C2TDC521080IPOE



- 2 Megapixel Full 1080p
- H.264 High Profile 4.2
- 12 IR LEDs
- 12VDC / POE
- Flush Mountable
- ONVIF Compliant
- 2 Year Warranty

H.264 High Profile 4.2 Compression

Most efficient compression technology



Fully compliant with ONVIF industry

Digital Zoom

Real Time Streaming Protocol (RTSP)

Allows for compatibility with media players such as Apple QuickTime®, Windows Media Player®, VLC Player®,

Alarm Contacts

- Direct Input/Output triggers
- RS485 output
- Trigger alarm events to PTZ

Viewbiquity M2M (Machine to Machine) Compliance

www.viewbiquity.com

standards

Zoom live or after event while recording full field of view in HD

Multi-Streaming

available

More storage

- Up to 3 simultaneous independent streams
- Two H.264, One MJPEG

Better picture quality

Fast MegaPixel Image Rates

Each stream configurable independently

Up to 30fps in Full HD 1080p Mode

- Frames per second
- Resolution
- Quality
- Send to different source

Mini SD Slot

- Record directly to SD card on alarm
- Supports > 2gb card










Technical Specifications





| Camera | C2TDC521080IPOE |
|-----------------------------------|--|
| Resolution | Full HD 1080p |
| Effective Pixels (H x V) | 1980 x 1080, 1280 x 720, 640 x 360 |
| Video Compression | H.264 High Profile Level 4.2, MJPEG |
| Image Sensor | Progressive Scan CMOS with Removable ICR, True Day/Night |
| Frame Rate | Up to 30 frames per second in Full HD 1080p Mode |
| Network | 10/100 Base-T (RJ-45) |
| Alarm Contacts | 1 Channel Input / Output |
| Audio | Full Duplex Audio Connection (mic and speaker sold separately) |
| Audio Compression | G.711 |
| Storage | Record to ONVIF NVR, FTP, NFS, CIFS, or Mini SD |
| Privacy Masking | Yes |
| Protocol | ONVIF |
| Network Protocol | SMTP – Email Notification, Multi-Casting, RTSP / RTP / RTCP, TCP / UDP, HTTP, DHCP, PPPoE, DDNS, NTP |
| Minimum Illumination | 1 Lux / F1.2 w/o IR 0.0 Lux with IR |
| Megapixel Varifocal Lens Included | 2.8-10 mm |
| Infrared | 12 IR LED's, 10-15M Distance |
| Motion Detection | Yes |
| Analog Video Output | Yes |
| Power Requirements | 12VDC / PoE |











Underside Base hole positions Recess Mount Fitting dimensions



800.873.5528 WWW.TARGETD.COM