

TARGET
DISTRIBUTING

888.792.7463
WWW.TARGETD.COM

SouthWest USA & Mexico
140 Caspian Court
Sunnyvale, CA 94089
Phone: 760-736-8000

**Eastern/North Central USA
& Central/South America**
134 Cherry Creek Circle
Winter Springs, FL 32708
Phone: 407-366-6490
Fax: 407-366-5945

**NorthEastern USA
& Canada**
620 Herndon Pkwy
Suite 200
Herndon, VA 22070
Phone: 703-481-9828
Fax: 703-437-9215

Europe
Swords Co.
Unit 100 Airside Business Park
Dublin, Republic of Ireland
Phone: +353 (0)1-813-6070
Fax: +353 (0)1-813-6071

Central & Southern Europe
Rudolf-Diesel-Str. 3
40822 Mettmann, Germany
Phone: 49-210-495-3433
Fax: 49-210-495-3434

Korea
#14-202, Anyang International
Distribution Complex,
555-9 Hoggie-dong, Dongan-gu
Anyang City, Kyonggi-Do
Phone: +82-31-479-0507
Fax: +82-31-479-0509

Japan
Nisso 15 Bldg. 8F
2-17-19 Shin-Yokohama,
Kohoku-ku
Yokohama 222-0033
Phone: 81-45-474-0181
Fax: 81-45-474-0371

Asia/Pacific Rim
Suite 902 - 903
Bank of East Asia Harbour View Centre
56 Gloucester Road
Wanchai
Hong Kong
Phone: 852-2712-0501
Fax: 852-2712-9385

SanDisk 

SanDisk, the SanDisk logo, SanDisk Ultra, and CompactFlash are trademarks of SanDisk Corporation, registered in the United States and other countries. Store Your World in Ours and iNAND are trademarks of SanDisk Corporation. SanDisk is an authorized licensee of the SD trademark. Memory Stick PRO, Memory Stick PRO Duo and MagicGate are trademarks of Sony Corporation. RS-MMC is a trademark of the MultiMediaCard Association. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s).

©2005 SanDisk Corporation. 80-11-00186 Rev.18, 12/05

Flash Memory Storage Solutions From the Worldwide Flash Card Leader.



SanDisk 
STORE YOUR WORLD IN OURS™



	CompactFlash	SanDisk Ultra II CompactFlash
Interface	PC Card ATA True IDE Mode	PC Card ATA True IDE Mode
Performance (Notes 1 & 2) Interface Transfer Speed (Max)	16.6 MB/sec	16.6 MB/sec
Power Requirements (Note 1) DC Input Voltage	3.3V ± 5%, 5V ± 10%	3.3V ± 5%, 5V ± 10%
Typical Power Dissipation (Notes 3 & 4)		
Sleep	300 µA (3.3V)	500 µA (5V)
Read (Typical)	<50 mA RMS (3.3V)	<55 mA RMS (5V)
Write (Typical)	<65 mA RMS (3.3V)	<70 mA RMS (5V)
Environmental Specifications		
Temperature		
Operating Commercial	0–70°C	0–70°C
Non-Operating Commercial	–25–85°C	–25–85°C
Humidity		
Operating	8–95%, non-condensing	8–95%, non-condensing
Non-Operating	8–95%, non-condensing	8–95%, non-condensing
Acoustic Noise (at 1 meter)	0 dB	0 dB
Vibration		
Operating	15 G peak to peak max.	15 G peak to peak max.
Non-Operating	15 G peak to peak max.	15 G peak to peak max.
Shock		
Operating	2,000 G max.	2,000 G max.
Non-Operating	2,000 G max.	2,000 G max.
Altitude (relative to sea level)		
Operating/Non-Operating	80,000 feet max.	80,000 feet max.
Reliability and Maintenance		
MTBF (Mean Time Between Failures)	>1,000,000 hours	>1,000,000 hours
Preventive Maintenance	None	None
Data Reliability	<1 non-recoverable error in 10 ¹⁴ bits read	<1 non-recoverable error in 10 ¹⁴ bits read
Physical Specifications	CompactFlash	Ultra II CompactFlash
Length	1.433 in (36.4 mm)	1.433 in (36.4 mm)
Width	1.685 in (42.8 mm)	1.685 in (42.8 mm)
Height (Body)	0.130 in (3.30 mm)	0.130 in (3.30 mm)
Height (Removable Edge)	0.155 in (3.94 mm)	0.155 in (3.94 mm)
Weight	0.40 oz (11.4 g)	0.40 oz (11.4 g)
Ordering Information		
Order Model	SDCFJ-YYY	SDCFH-YYY
YYY:	64 64.2 MB 128 128.4 MB 256 256.9 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB 4096 4096.3 MB	1024 1024.9 MB 2048 2048.9 MB 4096 4096.3 MB 8192 8192.6 MB 16384 16384.0 MB

Specifications subject to change without notice

Other versions available:
B: Standard
H: “Ultra” High-Speed
J: MLC/NAND
I: Industrial Temperature
Note: Capacities may vary by product family. Consult your SanDisk Sales Representative for correct ordering part numbers.

Note 1: All values quoted are typical at ambient temperature and nominal supply voltage unless otherwise stated.

Note 2: All performance timing assumes the controller is in the default (i.e., fastest) mode.

• **SanDisk CompactFlash®**

SanDisk CompactFlash revolutionized handheld electronics with unprecedented functionality when CompactFlash was first invented. The CompactFlash memory card’s matchbook size and half-ounce weight make it the ideal solution for small devices that need high capacity flash memory. Today, the CompactFlash storage specification is the industry-standard for next-generation, small form factor consumer applications such as digital cameras and handheld PCs that need very high capacities. CompactFlash is available in capacities up to 4GB* and the SanDisk Ultra® II CompactFlash is available in capacities up to 16GB.



• **SanDisk RS-MMC™ (Reduced-Size MultiMediaCard)**

The SanDisk RS-MMC is designed for use in the newest generation of ultra-small mobile phones. It is about half the size of a standard MultiMediaCard, and has the same simple, low power interface. This allows the RS-MMC to be used with an extender in a full size MMC slot. The RS-MMC is available in 64MB, 128MB, 256MB, 512MB and 1GB capacities.



* 1 megabyte (MB) = 1 million bytes;
1 gigabyte (GB) = 1 billion bytes

• **SanDisk Memory Stick PRO Duo™ Card**

The SanDisk Memory Stick PRO Duo card provides high capacity memory with the data transfer speeds of the Memory Stick PRO Interface. It was designed for use in the newest generation of mobile phones, digital still cameras, video cameras, digital music players and other size-sensitive mobile devices. The Memory Stick PRO Duo cards are also very secure with Advanced MagicGate™ copy protection included. Available in 32MB, 64MB, 128MB, 256MB, 512MB, 1GB and 2GB capacities.



• **SanDisk iNAND™**

SanDisk iNAND is a single chip device ideal for storing audio, video, images and other data on small portable systems such as mobile phones, MP3 players and GPS devices. It has a simple, high-performance serial interface that follows the industry standard SD or SPI protocols. This allows iNAND to be seamlessly integrated into designs that already have a memory card slot. iNAND is available today in 256MB, 512MB, 1GB and 2GB capacities.



• **SanDisk USB Flash Drive (UFD)**

The SanDisk UFD is available in 64MB, 128MB, 256MB, 512MB, 1GB and 2GB capacities. It is Hi-Speed USB 2.0 compliant. This drive was specifically designed to allow unique customization on the label. The SanDisk UFD is slim enough to plug into any USB port without obstructing adjacent ports.



SD Card					
SD Card			SanDisk Ultra II SD Card		
	microSD	SD Card		SanDisk Ultra II SD Card	miniSD
Interface	SD or SPI	SD or SPI	Interface	SD	SD or SPI
Performance (Notes 1 & 2) Interface Transfer Speed (Max)	25 MB/sec	25 MB/sec	Performance (Notes 1 & 2) Interface Transfer Speed (Max)	25 MB/sec ≥256 MB	25 MB/sec ≥256 MB 12.5 MB/sec ≤128 MB
Power Requirements (Note 1) DC Input Voltage	2.7V-3.6V	2.7V-3.6V	Power Requirements (Note 1) DC Input Voltage	2.7V-3.6V	2.7V-3.6V
Typical Power Dissipation (Notes 3 & 4)			Typical Power Dissipation (Notes 3 & 4)		
Sleep	150 µA	250 µA	Sleep	250 µA	150 µA
Read	50 mA	70 mA	Read	75 mA	50 mA
Write	60 mA	80 mA	Write	75 mA	60 mA
Environmental Specifications			Environmental Specifications		
Temperature			Temperature		
Operating Commercial	-25~85°C	-25~85°C	Operating Commercial	-25~85°C	-25~85°C
Non-Operating Commercial	-40~85°C	-40~85°C	Non-Operating Commercial	-40~85°C	-40~85°C
Humidity			Humidity		
Operating	25°C/85% rel. humidity	25~95%, non-condensing	Operating	25~95%, non-condensing	8~95%, non-condensing
Non-Operating	40°C/85% rel. humidity	25~95%, non-condensing	Non-Operating	25~95%, non-condensing	8~95%, non-condensing
Acoustic Noise (at 1 meter)	0 dB	0 dB	Acoustic Noise (at 1 meter)	0 dB	0 dB
Vibration			Vibration		
Operating	15 G peak to peak max.	15 G peak to peak max.	Operating	15 G peak to peak max.	15 G peak to peak max.
Non-Operating	15 G peak to peak max.	15 G peak to peak max.	Non-Operating	15 G peak to peak max.	15 G peak to peak max.
Shock			Shock		
Operating	1,000 G max.	1,000 G max.	Operating	1,000 G max.	1,000 G max.
Non-Operating	1,000 G max.	1,000 G max.	Non-Operating	1,000 G max.	1,000 G max.
Altitude (relative to sea level)			Altitude (relative to sea level)		
Operating/Non-Operating	80,000 feet max.	80,000 feet max.	Operating/Non-Operating	80,000 feet max.	80,000 feet max.
Reliability and Maintenance			Reliability and Maintenance		
MTBF (Mean Time Between Failures)	>1,000,000 hours	>1,000,000 hours	MTBF (Mean Time Between Failures)	>1,000,000 hours	>1,000,000 hours
Preventive Maintenance	None	None	Preventive Maintenance	None	None
Data Reliability	<1 non-recoverable error in 10 ¹⁴ bits read	<1 non-recoverable error in 10 ¹⁴ bits read	Data Reliability	<1 non-recoverable error in 10 ¹⁴ bits read	<1 non-recoverable error in 10 ¹⁴ bits read
Physical Specifications			Physical Specifications		
Length	11 mm	32 mm	Length	32 mm	21.5 mm
Width	15 mm	24 mm	Width	24 mm ± 0.08 mm	20.0 mm
Height (Body)	1.0 mm	2.1 mm	Height (Body)	2.1 mm ± 0.1 mm	1.4 mm
Height (Removable Edge)	N/A	N/A	Height (Removable Edge)	N/A	N/A
Weight	0.40 g. max.	2.0 g. max.	Weight	2.0 g. max.	1.0 g. max.
Ordering Information			Ordering Information		
Order Model #	SDSDQ-YYY	SDSDJ-YYY	Order Model #	SDSDH-YYY	SDSDM-YYY
YYY:	64 64.2 MB 128 128.2 MB 256 256.2 MB 512 512.4 MB 1024 1024.9 MB	64 64.2 MB 128 128.2 MB 256 256.2 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB	YYY:	1024 1024.9 MB 2048 2048.9 MB	64 64.2 MB 128 128.2 MB 256 256.2 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB
Specifications subject to change without notice			Specifications subject to change without notice		
Note 1: All values quoted are typical at ambient temperature and nominal supply voltage unless otherwise stated.			Note 2: All performance timing assumes the controller is in the default (i.e., fastest) mode.		
			Note 3: Sleep mode currently is specified under the condition that all card inputs are static CMOS levels and in a “Not Busy” operating state.		
			Note 4: The currents specified show the bounds of programmability of the product.		

SanDisk offers a broad range of flash data

storage products, including memory modules,

CompactFlash®, SD™, miniSD™, microSD™,

RS-MMC™, USB and Memory Stick PRO Duo™.

All of these products share the leading edge

technology for which SanDisk is known.

SanDisk is the inventor or co-developer of most of

the flash memory card form factors on the market

today, including CompactFlash, MultiMediaCard,

SD, Memory Stick PRO™, iNAND™ and microSD.

In 2000, SanDisk entered into a joint flash

fabrication venture called FlashVision LLC, which

produces NAND wafers at a plant located in

Yokkaichi, Japan. In 2002, SanDisk launched the

world's first Multi-Level Cell NAND-based flash

memory products, and today SanDisk is one of

only two companies manufacturing MLC NAND

flash memory.

Beyond the core flash memory technology, SanDisk

continues to evolve flash card functionality and

performance levels to meet the needs of emerging

applications such as mobile phones, PDAs, portable

audio, digital video, digital imaging and more. This

brochure highlights all of the products currently

available for OEM customers. For more accurate

and up-to-date product information and

specifications, please visit the SanDisk website at

www.sandisk.com.

• SanDisk microSD™ Card

Measuring just 11mm by 15mm and 1mm thick, the SanDisk microSD card is the ultimate storage solution for the next generation of increasingly compact mobile phones. Two-thirds

the size of a SIM module, microSD card are even smaller than many embedded memory devices. Available in capacities ranging from 64MB to 1GB, the SanDisk microSD card gives mobile phone designers and manufactures more flexibility.

In addition, the SanDisk microSD removable card makes it easy for mobile phone users to transport their personal content like saved photos, music files, high fidelity ring tones, applications, and system settings from one mobile phone to another when they need to upgrade their phone or service.



• SanDisk SD™ Card

The SD card is a flash memory storage device designed to meet the security, capacity and performance requirements inherent in the latest consumer electronics devices. Key enhancements over the MultiMediaCard include cryptographic security for protection of copyrighted data, more than a 5X improvement in maximum data transfer rate, and a user selectable write protect switch on the card casing. The standard SD is offered in capacities from 64MB to 2GB and the SanDisk Ultra II SD is available in 1GB and 2GB capacities.



• SanDisk miniSD™ Card

The miniSD card is designed specifically to meet the needs of today's small mobile phones. SanDisk miniSD is based on the popular SD card. It uses the same powerful, simple, high performance interface SD offers. The miniSD offers full compatibility and interoperability with any SD host by using an available passive adapter. The SanDisk miniSD card is available in capacities from 64MB to 2GB.



	RS-MMC	Memory Stick PRO Duo
Interface	MultiMediaCard or SPI	Memory Stick PRO

Performance (Notes 1 & 2) Interface Transfer Speed (Max)	2.5 MB/sec	20 MB/sec
---	------------	-----------

Power Requirements (Note 1) DC Input Voltage	2.7V-3.6V	2.7V-3.6V
---	-----------	-----------

Typical Power Dissipation (Notes 3 & 4)			
Sleep	150 µA	Typical	Max
Read	50 mA	125 µA	1 mA
Write	60 mA	<50 mA	65 mA
		<75 mA	100 mA

Environmental Specifications		
Temperature		
Operating Commercial	-25-85°C	-25-85°C
Non-Operating Commercial	-40-85°C	-40-85°C
Humidity		
Operating	8-95%, non-condensing	25-85%, non-condensing
Non-Operating	8-95%, non-condensing	Max 95% (saturated state)
Acoustic Noise (at 1 meter)	0 dB	0 dB
Vibration		
Operating	15 G peak to peak max.	15 G peak to peak max.
Non-Operating	15 G peak to peak max.	15 G peak to peak max.
Shock		
Operating	1,000 G max.	1,000 G max.
Non-Operating	1,000 G max.	1,000 G max.
Altitude (relative to sea level)		
Operating/Non-Operating	80,000 feet max.	80,000 feet max.

Reliability and Maintenance		
MTBF (Mean Time Between Failures)	>1,000,000 hours	>1,000,000 hours
Preventive Maintenance	None	None
Data Reliability	<1 non-recoverable error in 10 ¹⁴ bits read	<1 non-recoverable error in 10 ¹⁴ bits read

Physical Specifications		
Length	18 mm	20 mm
Width	24 mm	31 mm
Height (Body)	1.4 mm	1.6 mm
Height (Removable Edge)	N/A	N/A
Weight	1.0 g. max.	2.0 g. max.

Ordering Information		
Order Model #	SDMJ-YYY	SDMSPD-YYY
YYY:	64 64.2 MB 128 128.4 MB 256 256.9 MB 512 512.4 MB 1024 1024.9 MB	64 64.2 MB 128 128.4 MB 256 256.9 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB

Note 3: Sleep mode currently is specified under the condition that all card inputs are static CMOS levels and in a "Not Busy" operating state.

Specifications subject to change without notice

Note 4: The currents specified show the bounds of programmability of the product.

	iNAND
Interface	SD or SPI

Performance (Notes 1 & 2) Interface Transfer Speed (Max)	25 MB/sec
---	-----------

Power Requirements (Note 1) DC Input Voltage	2.7V-3.6V
---	-----------

Typical Power Dissipation (Notes 3 & 4)	
Sleep	250 uA
Read	65 mA
Write	75 mA

Environmental Specifications	
Temperature	
Operating Commercial	-25-85°C
Non-Operating Commercial	-40-85°C
Humidity	
Operating	8-95%, non-condensing
Non-Operating	8-95%, non-condensing
Acoustic Noise (at 1 meter)	0 dB
Vibration	
Operating	15 G peak to peak max.
Non-Operating	15 G peak to peak max.
Shock	
Operating	1,000 G max.
Non-Operating	1,000 G max.
Altitude (relative to sea level)	
Operating/Non-Operating	80,000 feet max.

Reliability and Maintenance	
MTBF (Mean Time Between Failures)	>1,000,000 hours
Preventive Maintenance	None
Data Reliability	<1 non-recoverable error in 10 ¹⁴ bits read

Physical Specifications	
Length	18 mm
Width	12 mm
Height (Body)	1.2 mm max (256 & 512 MB/1 GB) 1.4 mm (2 GB & 4 GB)
Height (Removable Edge)	N/A
Weight	0.40 g. max.

Ordering Information	
Order Model #	SDINB1-YYY
YYY:	256 256.2 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB

Specifications subject to change without notice