

888.792.7463 **WWW.TARGETD.COM**

ErisTerminal® SIP Deskset

VSP725

It's business as usual with the VSP725 deskset. Installation is easy and cost-effective with Power over Ethernet (PoE) support, dual Ethernet ports and auto-provisioning. Program up to 24 buttons for one-touch access to shared call appearances, busy lamp fields, quick dial keys, paging and more. Manage multiple calls with advanced call handling features and support for up to three SIP lines/accounts. Support for the G.722 wideband codec for HD Audio means you'll enjoy superior voice quality too.



VSP725 SIP Deskset Features¹

Power over Ethernet (PoE) support (AC adapter included) Support for up to 3 SIP lines/accounts 200-name phonebook Supports 3 configurable soft keys 3-way local conference; N-way network conference 4-way navigational pad 10 selectable ringtones Automatic call distribution (ACD) Call log/list, history, caller ID support 14 programmable keys (2 pages x 12): feature keys or line appearances Intercom, redial Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Adjustable volume Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs Failover support and server redundancy SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq 2-position, desk- or wall-mountable Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning		
Power over Ethernet (PoE) support (AC adapter included) Support for up to 3 SIP lines/accounts 200-name phonebook Supports 3 configurable soft keys 3-way local conference; N-way network conference 4-way navigational pad 10 selectable ringtones Automatic call distribution (ACD) 24 programmable keys (2 pages x 12): feature keys or line appearances Intercom, redial Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Adjustable volume Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs Failover support and server redundancy SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq 2-position, desk- or wall-mountable Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	158×57 pixels (w \times h) backlit display	Do Not Disturb (DND)
Support for up to 3 SIP lines/accounts 200-name phonebook Supports 3 configurable soft keys 3-way local conference; N-way network conference 4-way navigational pad 10 selectable ringtones Automatic call distribution (ACD) 24 programmable keys (2 pages x 12): feature keys or line appearances Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Adjustable volume Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch 2-position, desk- or wall-mountable Auto answer Supports custom logos Hold, mute Supports WebUI customization (user and administrator) Shared call appearances (SCA)	Dual Ethernet ports, 10/100 Mbps	Call transfer, call park, call pickup
Supports 3 configurable soft keys 4-way navigational pad 10 selectable ringtones Automatic call distribution (ACD) 24 programmable keys (2 pages x 12): feature keys or line appearances Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Adjustable volume Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs Failover support and server redundancy SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband®, Metaswitch QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq 2-position, desk- or wall-mountable Auto answer Supports custom logos Hold, mute Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	Power over Ethernet (PoE) support (AC adapter included)	Paging
4-way navigational pad 10 selectable ringtones Automatic call distribution (ACD) 24 programmable keys (2 pages x 12): feature keys or line appearances Intercom, redial Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs Failover support and server redundancy SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch 2-position, desk- or wall-mountable Auto answer Hold, mute Supports Custom logos Hold, mute Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	Support for up to 3 SIP lines/accounts	200-name phonebook
Automatic call distribution (ACD) 24 programmable keys (2 pages x 12): feature keys or line appearances Intercom, redial Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Adjustable volume Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq 2-position, desk- or wall-mountable Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) 3-year warranty	Supports 3 configurable soft keys	3-way local conference; N-way network conference
24 programmable keys (2 pages x 12): feature keys or line appearances Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs Failover support and server redundancy SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq 2-position, desk- or wall-mountable Auto answer Supports auto IP provisioning, IPv4, DHCP Client, DNS, HTTPS, SNTP Client Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) 3-year warranty	4-way navigational pad	10 selectable ringtones
Full-duplex speakerphone Auto-dial/quick dial keys Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Adjustable volume Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs Failover support and server redundancy SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq 2-position, desk- or wall-mountable Supports auto IP provisioning, IPv4, DHCP Client, DNS, HTTPS, SNTP Client Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	Automatic call distribution (ACD)	Call log/list, history, caller ID support
Message waiting indicator 2.5 mm corded headset jack Supports corded and cordless DECT headset Adjustable volume Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch 2-position, desk- or wall-mountable Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA)	24 programmable keys (2 pages x 12): feature keys or line appearances	Intercom, redial
Supports corded and cordless DECT headset Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs Failover support and server redundancy SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch 2-position, desk- or wall-mountable Supports auto IP provisioning, IPv4, DHCP Client, DNS, HTTPS, SNTP Client Auto answer Hold, mute Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	Full-duplex speakerphone	Auto-dial/quick dial keys
Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch 2-position, desk- or wall-mountable Supports auto IP provisioning, IPv4, DHCP Client, DNS, HTTPS, SNTP Client Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	Message waiting indicator	2.5 mm corded headset jack
SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch 2-position, desk- or wall-mountable Auto answer Hold, mute Busy Lamp Field (BLF) Supports custom (BLF) Supports Custom (SCA) Supports WebUI customization (user and administrator) 3-year warranty	Supports corded and cordless DECT headset	Adjustable volume
2-position, desk- or wall-mountable Auto answer Supports auto IP provisioning, IPv4, DHCP Client, DNS, HTTPS, SNTP Client Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	Supports HD Voice and G.711, G.726, G.729 and G.722 wideband codecs	Failover support and server redundancy
Auto answer Supports custom logos Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	SIP compatibility: Asterisk-based platforms, Broadsoft®, Genband™, Metaswitch	QoS: 802.1x, DiffServ (DSCP, TOS), STUN, VLAN 802.1pq
Hold, mute Supports custom default file for provisioning Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	2-position, desk- or wall-mountable	Supports auto IP provisioning, IPv4, DHCP Client, DNS, HTTPS, SNTP Client
Busy Lamp Field (BLF) Supports WebUI customization (user and administrator) Shared call appearances (SCA) 3-year warranty	Auto answer	Supports custom logos
Shared call appearances (SCA) 3-year warranty	Hold, mute	Supports custom default file for provisioning
	Busy Lamp Field (BLF)	Supports WebUI customization (user and administrator)
Call forward, call blocking	Shared call appearances (SCA)	3-year warranty
	Call forward, call blocking	

Specifications, weights & dimensions

Color: GM (Gun Metal)	Giftbox dimensions (WxDxH): 7.32" x 4.49" x 8.78"
SKU: 03041	Giftbox weight: 2.49 lbs.
Product dimensions (WxDxH): BS: 7.15" x 8.60" x 5.59" Corded HS: 8.09" x 1.99" x	Master pack dimensions (WxDxH): 15.32" x 9.65" x 9.49"
2.05" Corded HS on BS: 7.15" x 8.60" x 6.77"	Master pack weight: 11.73 lbs.
Product weight: 2.14 lbs.	Quantity: 4

VSP725 U.S. codes

APN: 80-9311-00





 $^{^{\}scriptsize 1}$ Features and functionality may vary, depending on SIP service provider and/or SIP phone system platform.

