

KX-UTG200

- HD Voice and Full Duplex Speaker Phone
- 3-line Color Graphical LCD
- Two Gigabit Ethernet, PoE
- Zero Touch Provisioning
- Two-year Warranty

Unmatched Voice Clarity and Reliability

The Panasonic KX-UTG200 SIP Phone is a cost-effective communication solution that's easy to use and manage. Delivering innovative technology and interoperability for business-class features, the Panasonic KX-UTG200 helps businesses improve productivity and enhance collaboration with HD voice and full duplex speakers. Making sure your business stays up and running is a top priority. The KX-UTG200 comes standard with our US-based two-year warranty.



800.873.5528
WWW.TARGETD.COM



KX-UTG200 Specifications

KX-UTG200 SPECIFICATIONS	
LCD Display	3.5-inch QVGA 320/240 Color Graphical TFT LCD
LCD Size	3.5-inch 320/240 pix
LCD Backlight	Level 1 – 14
INSTALL OPTIONS	
Desk Mount Tilt	Yes—2 Positions
Wall Mount	KX-A433-B
Power Adapter	DSA-42D-482480063
NETWORKING	
Ethernet Ports	2 Gigabit Ethernet
Power Over Ethernet (PoE)	Yes—Class 2
AUDIO FEATURES	
Handset, Speaker, Headset Volume	8 levels (includes echo cancellation and distortion prevention)
Ringtones	9
Ringer Volume	Total 9 levels (0 level is off)
Headset Port	RJ9
Electronic Hook Switch Control Port	RJ11 Jabra and Plantronics compatible
Hearing Aid	Compatible with Hearing Aid TIA-1083 / FCC P68.316 / FCC P68.317 / CS-03
Audio Codec	G.711 (A-law and μ -law), G.729AB, G.722, G.726
KEYS	
Keys (total)	41
Programmable Keys	24 keys (3 pages of 8)
Navigator Key	Yes
SOFTWARE FEATURES	
Phone Book Entries	1,000
Call Log Entries	4 lines (Each line: 100 Placed Call +100 Received Call +100 Missed Call)
Conferencing	3 parties (within terminal—multi-party dependent on server)
Music on Hold	Support
IP FEATURES	
SIP Accounts	4
SIP Compatibility	RFC 3261 Standard SIP Server, BroadSoft®, Metaswitch®, Digium®
IP Version	IPv4/IPv6
DHCP Client	Yes
DNS	Yes
HTTP	Yes
HTTPS	Yes
SNTP Client	Yes
VLAN (802.1q)	Yes
QoS (DiffServ)	Yes
sRTP/TLS	Yes
RTCP	Yes
TFTP/FTP	Yes
LLDP	Yes
CDP Compatible	Yes
NAT/STUN	Yes
Refer	Yes
Single Common Firmware/Auto Firmware	Yes
XML Provisioning	Yes
Web Setting/Service Mode	Yes
LDAP	Yes
802.1x	Yes

KX-UTG200 SPECIFICATIONS, CONT.	
CONFIGURATION	
Plug & Play Configuration	Server-based configuration, BroadSoft® Device Management Server and Metaswitch Network SIP Provisioning Server
Manual Configuration	Internal Web Configurator, Local (LCD based) Network Configuration
USB	No
AC Adapter	Support up to 30.24W
Operating Environment	32°F to 104°F (0°C to 40°C)
DIMENSIONS AND WEIGHT	
Lower Position	10.51" x 7.36" x 6.10" (W x D x H) (handset on cradle, stand attached)
High Position	10.51" x 6.69" x 7.08" (W x D x H) (handset on cradle, stand attached)
Weight	2.65873 lb. (with handset, handset cord and stand)
CALL FEATURES	
Shared Call/Line Appearance	Yes
Flexible Line Appearance	Yes
Call Transfer	Yes
Do Not Disturb	Yes
Call Forward (conditional/unconditional)	Yes
Conferencing (local/network)	Yes
Multi-cast Paging	Yes
Call Waiting	Yes
Call Park/Call Pickup	Yes
Speed Dial/Redial	Yes
Busy Lamp Field (BLF)	Yes



800.873.5528
WWW.TARGETD.COM

SOLUTIONS FOR UNIFIED COMMUNICATIONS