



C2TA52ULTRA



ClearNight Ultra Camera

The ClearNight Ultra camera is the industry leader in low-light camera technology. See **COLOR** images in almost complete darkness without the use of IR LED's and because of the Ultra's extended dynamic range, have more vivid colors in bright lighting.



ClearNight Ultra head-to-head against leading competitors in low light.

Check out the Ultra against the competition at
<http://www.clear2there.com/ultrademo>
and clearly see the difference!
(The Ultra is the upper right camera)



ClearNight Ultra head-to-head against leading competitors in bright light.

- 650 Lines of Color Resolution
- Minimum Illumination .0005 Lux in Color
- 3rd Generation 3D Noise Reduction - Eliminates Noise in Picture During Low Light Settings
- Dual Voltage – 12VDC/24VAC
- 2nd Video Out – Installer Port for Setup/Focus
- Wider Dynamic Range – Capture Images in Bright Lighting as Well as Low Light Areas
- 3x Faster Adjustment to Lighting Changes
- 3 Axis – Wall or Ceiling Mount
- 2.8-12mm Auto Iris Varifocal Lens
- Full OSD Operation



800.873.5528
WWW.TARGETD.COM

www.clear2there.com

Specifications:

Image Sensor	1/3" ClearNight Ultra
Resolution	650 TV Lines (Color) 700 TV Lines (B/W)
Minimum Illumination	0.0005 Lux (Color)
Effective Pixels	976 x 494
Lens Furnished	2.8-12mm Auto Iris
Sync. System	Internal
S/N Ratio	More than 52dB
Video Output	2 Vp-p / 75 Ohms
OSD	Yes
WDR	On / Off (Level Adjustable)
Backlight Compensation	BLC / HLC / Off
Gain Control	Multi-Level User Defined
White Balance	Multi-Level User Defined
Motion Detection	Yes
Privacy Masking	Yes (15 Programmable Zones)
Digital Noise Reduction (DNR)	Multi-Level User Defined
E-Zoom	Yes
DIS	On / Off
Sharpness	Multi-Level User Defined
Flip / Mirror	Yes (H, V, HV)
Power Supply (not included)	12VDC / 24VAC Dual Voltage
Operating Temperature	-10 - +50°C
Weight	1.9 lbs.
Specifications subject to change without notice and without incurring any obligation.	

Optional Accessories



C2TA5PEB

Pendant Mount



C2TA5WALL

Wall Mount



C2TA5CRNR**

Corner Mount



C2TA5POLE**

Pole Mount



C2TA5ADPT

2 Gang Box
Adapter Plate

** Requires C2TA5WALL or C2TA5PEB Mounts

Rev. 7-12