EnGenius

DuraFon-OHC

Datasheet

Key Features

- + Range up to: 12 floors (office), or 250,000 sq. ft. (retail)
- + Speakerphone in handset
- + 2-Way handset-to-handset communication, independent of base station
- + 2.5 mm headset port
- + 50 hours stand by time
- + Up to 6 hours of talk time
- + Sleek design
- Signal range that greatly exceeds DECT or Wi-Fi phones.

Long-Range Office Cordless Phone Handset

Immediate workplace and large property mobility with unmatched wireless coverage with easy set up and usability.

The EnGenius DuraFon-OHC is a long-range, office style, cordless phone and two-way radio handset. With a range up to: 12 floors, or 250,000 sq. ft. This office version is compatible with and provides the same long range function as the rugged EnGenius DuraFon 1X or PRO handsets. The DuraFon-OHC is ideal for expansive properties such as hotels and resorts, schools, retail locations, or administrative offices. This stylish handset works with either the 4-line DuraFon PRO, or single-line DuraFon 1X base station. From one up to ninety handsets can be supported on DuraFon systems, making them excellent choices for organizations with mobile personnel. The DuraFon-OHC handset provides a stylish, long range, wireless extension with a stand-alone DuraFon base unit or behind an (IP) PBX.





Technical Specifications

Electrical Specifications

902 - 928 MHz Frequency

RF Power

Peak: 708mW Average: 80mW

200 kHz Channel Spacing Number of Channels: 128 **MSK Modulation** Freq. Hopping TDMA Freq. Hopping Rate: 100 per second TDMA Frame Length: 10ms Number of Slots / Frames: 2 Number of Users/Carrier: 1 Reciever Sensitivity < -108 dBm (@ BER 10-2)

Antenna Connector Connector: Non-standard

Antenna Gain: 2 dBi (Long) / 0.5 dBi (Low Profile)

Antenna Gain

Base Unit:	2 dBi Standard Dipole Antenna
	3 dBi Indoor external Antenna Option
	6 dBi External Outdoor Antenna
Handset:	2 dBi Tall Hanset Antenna
	0.5 dBi Low Profile Anntenna

TX Power Control Range: 100-708 mW Telephone Interface: N/A Speech Coding: 8 kbps G.729A Channel Coding: 8 kbps Convolutional + CRC Transmission Data Rate: 170.678 kbps User Data Rate: 128 kbps duplex Time Division Duplex (TDD) TIA / EIA -470B Voice Quality Number of System ID: 65,536 Auto-Attendant Coding: 8 kbps G.729

Power Source

3.7V, 1100 mAh Li-Ion Battery Charger Current: 500 mA 4 Hours (from empty) Charge Time



800.873.5528 WWW.TARGETD.COM TGSALES@TARGETDIST.COM

Actual signal range may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment, and mix of devices in the network. Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. For United States of America: Copyright © 2013 EnGenius Technologies, Inc. All rights reserved.

Environment & Mechanical

Regulation Compliance FCC Part 15 B/C, IC

Temperature Range Operating: 14 to 140°F / -10 to 60°C Storage: 14 to 158°F / -10 to 70 ° C

Humidity (non-condensing) 20% to 75%

Dimensions 1.8" x 1.3" x 7.6" (58 x 31 x 161 mm)

Weight Handset: 0.29lbs

Package Contents

DuraFon-OHC Handset Desktop Charger AC Adapter Belt Clip Battery Long Antenna Quick Install Guide Warranty Card Need Help Sheet CD with User Manual