

SIP TRUNKING, WIRELESS IP DECT, AND MORE





SOPHISTICATION SIMPLIFIED

Innovative NEC takes the lead with state-of-the-art innovations sure to make your business communications more efficient, profitable, and enjoyable. Stylish additions to any work environment, all DSX telephone models feature built-in speakerphone, two-position angle adjustment, and built-in wall mounting. Enhanced models also offer a backlit display and illuminated dial pad. Right out of the box, the system offers an innovative built-in Automated Attendant which can answer calls, play a greeting, and allow callers to directly dial extensions and departments without assistance. Also built-in is the ability to record a custom message for callers on hold.

Full-Featured VolP DSX provides cost-effective SIP Trunking with over a dozen certified providers from which to choose. Install DSX IP keysets on-premise or off-site in a remote office. Peer-to-peer connections conserve resources, and built-in NAT Traversal makes remote IP extension set up a breeze. Choose between the 34-Button Backlit Display and the 34-Button Backlit Super Display offering the same features as their digital counterparts as well as Full Duplex speakerphones. Compliant third-party SIP phones, soft phones, and Analog Telephone Adapters (ATAs) are also supported.

DSX Mobile IP Extension lets employees on the go use their smartphone to stay in touch with co-workers and associates. Mobile IP Extension uses a softphone (such as Counterpath's Bria) on an iPhone or Android smartphone as a DSX IP extension. The mobile extension connects to the office WiFi network when the user is at work and automatically re-registers over the cellular network while they travel. The basic operation of the Mobile IP Extension never changes, regardless of location.

Affordable and Reliable Designed with affordability and scalability in mind, DSX is sized right – from the economical DSX-40 to the DSX-80/160. All DSX-80 cards can be migrated to the DSX-160. Even when growing from the DSX-40, your investment in IntraMail, programming, telephones, and other station equipment is retained. Since DSX is simple to install and easy to use, the expenses of configuration, programming, and post-installation training are minimized. Additionally, the core DSX call processing features are mature, efficient, and reliable – yet intuitive and easy to use.

PUT INTRAMAIL TO WORK FOR YOU

IntraMail The ability to add voice mail is built into the system and only requires a compact flash card to activate. IntraMail is a full-featured Voice Mail Auto Attendant system that will greet and transfer callers and record voice mail messages. With built-in voice prompt guidance in English, Spanish, and French, IntraMail is a great fit in multilingual environments. From 2 to 8 voice mail ports are available and easily upgraded through licensing. IntraMail features include:

- Message Center Notify extension groups of important messages visually, using a message center key.
- Directory Dialing Dial a name instead of a number to reach your party.
- Message on Hold Record your own informative company message.
- Caller ID Caller information is verbally provided with a voice mail message.
- Conversation Record Save and record conversations with the touch of a button.
- Live Call Screening Listen as callers leave a message and pick up to answer.

IntraMail Pro Supports all of the features of IntraMail plus:

- *Email Integration* Receive notification of a new voice mail message to your email inbox. Notification includes the caller's number and name and can optionally include the recorded message as a .WAV file attachment. Additionally, Email Integration can automatically dispose of a new message when it is sent. The email disposition options include *Save When Sent* (save the voice message once the email is sent) and *Erase When Sent* (conversely erase the voice message).
- *Email Synchronization* The status of the voice mail message is automatically updated when you open the email and is displayed in the message. The voice mail message will be marked as listened to and will be saved or erased based on the user's preferences. There is no additional setup or special email requirements. Email Synchronization works with all types of email accounts (client or web-based).
- *Cascading Message Notification* Cascading Message Notification can call you at up to five preset destinations to let you know a new voice mail message has arrived.
- *Park and Page* Allows a caller to page you without operator assistance. You can pick up the call from any extension.
- *Find Me Follow Me* The Automated Attendant can find you when you're not at your desk.
- *Wakeup Call* Great for Motels and Bed & Breakfast establishments, DSX can automatically deliver a wakeup voice message to a room guest at a designated time. Wakeup Calls are conveniently managed from the web-based Wakeup Call Manager at the front desk. The front desk can set new wakeups, change those that are currently scheduled, and review the status of wakeups that were answered or ignored.



Email Synchronization



FLEXIBLE, INTUITIVE SOLUTIONS FOR TODAY'S OFFICE

Built-in Caller ID The capability for Caller ID (with Call Waiting) is inherent in every DSX system. With Caller ID, you can identify incoming callers before the call is answered. The caller's name and number (if available) will appear simultaneously in the display.

Logging – Stores the name, number and time/date of received outside calls for easy review, save and redial.

Checking – A manager can view Caller ID information associated with a co-worker's line or extension.

Return Call – Easily return a call without manually re-entering the caller's number. Select from a list of choices or have the system automatically redial the call for you.

Analog Ports – Caller ID information can be sent to analog single line ports for use with customer-provided Caller ID accessories.

Wireless IP DECT The ML440 Wireless IP DECT handset and AP20 Access Point provide the convenience of mobility by combining the latest VoIP and DECT communication technologies. The ML440 and AP20 use WiFi friendly DECT 6.0 (1.9 GHz) technology, so they won't disrupt the office wireless network. A single AP20 accommodates 30 handsets and supports 10 simultaneous calls. The extendedcoverage solution, with support for up to 20 access points, provides seamless handover. DSX supports up to 32 ML440 handsets per system.

Phone Manager Administration Tool Users and administrators can easily customize the most frequently-used telephone features with DSX Phone Manager. There is no software to install - Phone Manager is built into DSX and is web-based. The intuitive interface gets the user up to speed right away with no special training required.

Customize Your Communication Solution Advanced telephone features include:

- Backlit Display and Illuminated Dial Pad¹ easy viewing in low light areas.
- Interactive Soft Keys that change function as you use your phone, allowing you to access to advanced features by just pressing a key.
- User Level Programming easy and intuitive guided menu system for customizing the features of your telephone.
- Hot Dial Pad dial a call without first lifting the handset or pressing keys.
- Dual color (red/green) LEDs to help easily distinguish between calls.
- Desk Stand adjustable for two different positions.
- Wall Mounting built-in for low-profile wall mounting capability.

22-Button Display

Offers a large display, programmable keys, and a built-in speakerphone - making this the most economical option without sacrificing convenience.

34-Button Super Display²

All the features of the 34-Button Display and offers our largest. most interactive display for advanced users. Unique light sensors adjust the phone's brightness based on room lighting



Wireless IP DECT

Cordless DECT

Offers mobility, plus many standard features of the wired telephone, including handsfree, 8 programmable feature keys with LEDs, and a backlit display. Range extendable via repeaters.

Wireless Headset Adapter¹ Provides seamless integration with Plantronics Wireless Headset Systems.



DSS Console For power users, provides another 60 dual color programmable keys.

¹Select models. ²Available in IP and digital telephone models.

DSX digital telephones and console are available in black or white. IP and cordless telephones are available in black only.

34-Button Display² The same features as the 22-Button Display, plus

and is enhanced with a

backlit display and

illuminated dial pad.

additional programmable keys,

DSX Specifications and Features

Specifications¹

Specifications			
DSX-40	Base	<u>Max</u> 1	
Digital Stations	8	24	
VoIP Stations ⁴		32	
VoIP Gateway Ports Analog Stations	2	8 18	
Lines	2 4	8	
SIP Trunks		8	
Door Box Ports	2	2	
DSX-80			
Slots		4	
Digital Stations		32	
VoIP Stations ⁴ VoIP Gateway Ports		32 16	
Analog Stations		32	
Lines		64	
SIP Trunks		16	
DSX-160			
Slots		8	
Digital Stations		96	
VoIP Stations ⁴		32 16	
VoIP Gateway Ports Analog Stations		96	
Lines		64	
SIP Trunks		16	
IntraMail			
Voice Mail Ports	2	4, 6, or 8	
Storage Hours ³		8, 16, or 32	
Subscriber Mailboxes		128	

General

One Pair Wiring
USB 2.0 (Full Speed)
10/100 BASE-TX Ethernet, Auto-MDIX
RS-232 Serial Port for SMDR

DSX Features

2-Position Telephone Angle Adjustment Account Codes Alphanumeric Display Ambient Light Sensor Attendant Position Auto Redial Auto Attendant (Built-in) Automatic Daylight Savings Time Adjustment Automatic Handsfree Automatic Ring Down Background Music Backlit Display (selected models) Barge In (Intrusion) Battery Backed-up Memory Call Coverage Keys Call Forwarding On and Off Premises Call Timer (with or without a key) Call Waiting / Camp-On Callback Caller ID (with Call Waiting) Caller ID Logging (CID with Return Call) Caller ID Manual Callback Caller ID to Single Line Telephones Class of Service Conference (up to 8 parties per conference) Conference, Meet-Me Conference, Unsupervised Cordless DECT Telephone Delayed Ringing Department Groups (for Ring and UCD Groups) Dial Number Preview Dial Tone Detection Direct Inward Dialing (with ANI/DNIS and DID Translation Name)2

©NEC Corporation of America 6555 N. State Hwy 161, Irving, Texas 75039 DSX is a trademark of NEC Corporation of America. Some features may be optional or available at a future date. Recording of phone calls is subject to varying state/federal laws. The information herein is subject to change without notice at the sole discretion of NEC.

Rev 3, 10/11, Printed in U.S.A.

Direct Station Selection (DSS) Direct Station Selection (DSS) Console Directed Call Pickup Directory Dialing with Search Distinctive Ring (ICM, CO, Ring Grp, Recall) Do Not Disturb Do Not Disturb Override Door Box (Analog) Extended Ringing Extension Hunting (Circular, Terminal, UCD) Extension Locking Flash Flexible Numbering Plan Forced Line Disconnect Group Call Pickup Group Listen Group Ring Handsfree and Handsfree Answerback Headset Compatibility Hold (with Recall Display) Hold and Park Programmable Recall Cycles Home Automation Integration (HAI-compatible)5 Hot Dial Pad Hotline Illuminated Dial Pad (selected models) Interactive Soft Keys Intercom Intercom Queue Key Internet Time Service ISDN / PRI² Language Selection Last Number Redial Line Groups Line Keys Line Queuing / Callback Line Scheduling Loop Keys Meet-Me Conference Message on Hold (Built-in) Message Waiting Microphone Mute Modem (Built-In) Monitor / Silent Monitor Music on Hold Names for Extensions and Lines NAT Traversal Night Service / Night Ring Off-Hook Signaling Paging (Internal and External) with Answer Paging, Multicast Park (with Recall Display) Park Orbit Recall Pickup Password Reset Utility PBX / Centrex Compatibility PC Program (System Administrator) Peer-to-Peer IP Extensions Phone Manager Prime Line Preference Privacy Privacy Release Groups Private Line PRI / ISDN² PRI Calling Party Number Pulse to Tone Conversion Remote IP Extensions Remote Programming Removing Lines and Extensions From Service Reverse Voice Over Ring / Message Lamp Ringdown Extension Ringing Line Preference Room Monitor Save Number Dialed Selectable Display Messaging Silent Monitor Single Line Telephones SIP Trunking Speakerphone



Jres Handle Handle

Speed Dial Split (Alternate) Station Message Detail Recording System Programming Backup and Restore System Programming Password Protection T1 Lines² Temperature Display Tie Lines2 Time and Date Toll Restriction Transfer (with Recall Display) Upgrades via License for VoIP Ports User Level Programming Voice Mail Voice Over VoIP Extensions Volume and Contrast Controls Walking Class of Service Wall Mount / Desk Stand (Built-in) Wireless Headset Adapter (WHA) Wireless IP DECT (ML440)

IntraMail Features

Announcement Message Answering Machine Emulation / Call Screen Auto Time and Date Stamp Autoplay Messages Automated Attendant Broadcast Message Caller ID (with Return Call) Centrex Transfer Conversation Record Directory Dialing Distribution Lists Email Integration with Name3 Email Synchronization³ External Transfer Fax Detection Find Me Follow Me3 Flexible Answering Schedules Interactive Soft Keys Message Center Mailbox Message Disposition³ Message Notification (Local and Remote) Message Notification (Cascading³) Multilingual Prompts (English, Spanish, French) Multiple Company Greeting (8) Number of Messages Displayed Park and Page Personal Greeting (3) Security Code (with Option) Single Digit Dialing System Administrator Upgrade Licenses for IntraMail Ports and IntraMail Pro Voice Mail Overflow Voice Prompting Messages Wakeup Call³

¹Capacities listed are system maximums and may be limited by system configuration.
²DSX-80/160 only.
³Requires IntraMail Pro.
⁴Connectivity limited by available VoIP Gateway ports.
⁵HAI-Compatible systems include Omni IIe, OmniPro II, Lumina, and Lumina Pro.

To find out more about the DSX contact your local NEC dealer, visit our website at www.necdsx.com, or call 800-365-1928.

Empowered by Innovation

